




## TILIS avec réducteur manuel PED 97/23/CE




**REDUCTEUR MANUEL FONTE**  
MECANISME GRAISSE A VIE  
MANŒVRE PAR VOLANT

DN	A	B	C	D	E
32	57	221	171	32	125
40	57	221	171	32	125
50	62	227	171	41	125
65	70	236	171	44	125
80	89	242	171	44	125
100	106	266	171	50	125
125	120	281	171	54	125
150	132	332	188	54	200
200	164	444	210	58	315
250	200	469	210	66	315
300	238	494	210	76	315



DN	A	B	C	D	E
32	57	221	171	32	125
40	57	221	171	32	125
50	62	227	171	41	125
65	70	236	171	44	125
80	89	242	171	44	125
100	106	266	171	50	125
125	120	281	171	54	125
150	132	332	188	54	200
200	164	444	210	58	315
250	200	469	210	66	315
300	238	494	210	76	315



**INOX 316L**

**EPDM/PTFE** T°C +5°/+100°  Fluides alimentaires, boissons, fluides pharmaceutiques et cosmétiques

**CORPS FONTE FGS**

PFA 10 bar (water) / PS (p.84)

**CORPS FONTE FGS**

PFA 10 bar (water) / PS (p.84)



**TILIS OREILLES DE CENTRAGE**

(1) PS maxi = 6 bar

Raccordement PN 6/10/16/ASA 150

DN	EPDM/PTFE	Kg
32/40	149G 063 550	8,0
50	149G 065 990	7,9
65	149G 065 991	8,1
80	149G 064 353	8,4
100	149G 434 66	9,2
125	149G 434 67	9,4
150	149G 040 031	11,3
200	149G 043 902 (1)	18,4
250	149G 428 10 (1)	22,1
300	149G 428 11 (1)	18,4




**TILIS OREILLES TARAUEES**

(1) PS maxi = 6 bar et PN16  
(2) PS maxi = 6 bar et PN10

Raccordement PN 10/16

DN	EPDM/PTFE	Kg
50	149G 065 992	7,7
65	149G 065 993	4,2
80	149G 065 994	9,4
100	149G 446 66	8,1
125	149G 446 67	9,2
150	149G 040 032	13,7
200	149G 446 69(1) 149G 038 880(2)	22,6
250	149G 446 70(1) 149G 038 881(2)	32,7
300	149G 446 71(1) 149G 040 025(2)	49,8

**INOX 316L POLIMIROIR**

**EPDM/PTFE** T°C +5°/+100°  Fluides alimentaires, boissons, fluides pharmaceutiques et cosmétiques

**CORPS FONTE FGS**

PFA 10 bar (water) / PS (p.84)

**CORPS FONTE FGS**

PFA 10 bar (water) / PS (p.84)



**TILIS OREILLES DE CENTRAGE**

(1) PS maxi = 6 bar

Raccordement PN 6/10/16/ASA 150

DN	EPDM/PTFE	Kg
32/40	149G 065 995	8,1
50	149G 065 996	8,0
65	149G 065 997	8,3
80	149G 065 998	8,7
100	149G 428 26	9,8
125	149G 428 27	10,5
150	149G 040 033	12,6
200	149G 047 924 (1)	22,2
250	149G 063 202 (1)	26,5
300	149G 428 31 (1)	21,6



**TILIS OREILLES TARAUEES**

(1) PS maxi = 6 bar et PN16  
(2) PS maxi = 6 bar et PN10

Raccordement PN 10/16

DN	EPDM/PTFE	Kg
50	149G 065 999	2,9
65	149G 066 000	4,2
80	149G 066 001	9,7
100	149G 411 46	6,5
125	149G 411 47	9,2
150	149G 040 034	11,0
200	149G 046 989(1) 149G 038 883(2)	20,0
250	149G 411 50(1) 149G 038 884(2)	25,2
300	149G 411 51(1) 149G 038 885(2)	21,0